

## **5 YEAR GUARANTEE**

### **GEOPANEL PVC CEILING WALL AND SHOWER PANELS**

Freefoam guarantees that in a domestic environment, from the date of purchase, that the Geopanel PVC ceiling wall and shower panels will not delaminate or crack.

Freefoam products are manufactured with care from the best materials, however, if the panels show any material or manufacturing fault within 5 years after purchase please contact your local Freefoam dealer where your purchase was made within 30 days of discovering the fault.

### **GUARANTEE CONDITIONS**

The guarantee applies only if the rules stated below are followed, and if the panels have been fitted in accordance with the manufacturer's installation instructions.

1. The claim must be accompanied by a copy of your receipt. Keep your receipt at all times.
2. The guarantee is not transferable.
3. Check all Freefoam panels and extrusions for visible defects before and during installation. As is general practice, panels and extrusions that have been installed are assumed to be accepted.
4. Before installation, the panels should be allowed to acclimatise in the room where they are to be installed for 24-48 hours.
5. Please follow the full installation instructions in the panel pack, or the guarantee will be invalid.
6. All expansion gaps and extrusions must be filled with Sealant when fitted in showers and wet areas.
7. Freefoam only recommends non solvent Sealant for Shower and Wet Area Installations. The guarantee is invalidated if No Sealant has been used to fully seal the panels in Wet Areas.
8. Timber Battens (45mm x 21mm) are recommended if walls are uneven, in new build homes, and in rooms subject to condensation such as bathrooms. Fit battens at a maximum distance of 500mm apart. Fix panels to battens using non solvent wall panel adhesive. If walls are flat, dry and clean panels can be fitted directly on to wall.
9. The panels may not be subjected to temperatures above 60°C. This has to be taken into consideration especially when installing illumination into the panels.
10. Panels are for internal use only. Panels must not be fitted externally or exposed to any external elements such as acidic rain or direct UV sunrays.
11. To keep the panels in good condition they need to be cleaned on a regular basis. For this purpose, it is recommended to use a cleaner such as "Geopanel Cleaner", which is non-abrasive and anti-fungicidal.
12. Abrasive cleaners and cleaners containing bleach must not be used.
13. If the problem is a manufacturing fault, The Freefoam guarantee is limited to the supply of new panels of similar quality. Your local Freefoam dealer will handle your claim once authorised.
14. The guarantee does not cover ingress of water where the panels have not been fully sealed with Sealant, including any cuts in the panels such as for mounting accessories in a shower or if the seal or surface has been subsequently damaged or broken.

This guarantee is subject to the standard terms of sale as permitted by law and does not affect your statutory rights. Freefoam Building Plastics Ltd. reserves the right to alter the technical specifications in their literature.

Due to the limitations of the printing process, colours may vary from those in Freefoam brochures and marketing materials.

February 2016