





Plass4 Coupling (Universal) 25 × 15–22

Item # 77017251

Technical Drawing Dimensions

Product Code	d1 [mm]	d [mm]	H [mm]	E [mm]	E1 [mm]	l [mm]	l1 [mm]	Unit Per Bag	Unit Per Carton	Weight [g]
77017251	15–22	25	165	54	64	58	80	1	90	183

Product Specifications	Product Features		
Product Code	77017251	Nut Material	Polypropylene, high-grade copolymer.
Weight [g]	183	Split Ring Material	Polyacetal
Unit Per Carton	90	Seal Material	NBR
Nominal Diameter Mains [mm]	25	Product Components	2 Split Rings, 2 Seals, 2 Nuts
Product Name	Plass4 Coupling (Universal) 25 x 15–22	Pressure Rating Water	PN 16
Unit Per Bag	1	Nominal Diameter Outlet [mm]	15–22
Body Material	Polypropylene, high-grade copolymer.		

Product Specifications

Product Features

Standards

ISO 17885 for Water Applications, AS/NZS 4129, ISO 7/1, BS 21, DIN 2999, UNI 9561, NEN 3258, AS 1722, DIN 8076

Chemical Resistance

Polyacetal split rings and NBR o-rings, suitable for water, are supplied as standard. CPVC split rings and EPDM or FPM o-rings and seals are available. For aggressive chemical applications, the end user is advised to test suitability.

Operating Temperatures

Maximum temperature of use for fittings and valves is the same as that for polyet hylene pipe and they are not intended for use in hot water applications. They will withstand sub-zero temperatures.